

Halotron-1™ Stored Pressure Extinguisher Models

*If experiencing delays, downtime and interruptions is simply **not an option**, Halotron-1 is the choice.*

These quality fire extinguishers contain an extremely versatile and effective multipurpose clean extinguishing agent able to address most fire risks typically found in commercial and industrial applications. It is ideally suited for computer rooms, data storage, telecommunication, robotics or any high tech industrial process that requires an effective clean agent having an extended discharge range.

Halotron-1 is an environmentally acceptable Halon-1211 alternative. Larger sized models are suitable for use on Class A, B and C fires.

**2.5HB****11HB**

*The **ULTIMATE** in fire protection
for providers of essential services:
No clean-up • Reduces delays & downtime*

*Halotron-1 is the most effective
portable extinguisher "clean agent"
having Class A, B and C fire capability!*

BADGER*Extra* Halotron-1™ Features

- 2.5, 5, 11 and 15.5 pound models
- Chrome plated brass valves
- Stainless steel handles, levers & hose bands
- Large loop stainless steel pull pins with tether
- Steel internal siphon tubes
- Welded carbon steel cylinders
- Hex plated brass hose fittings
- Heavy duty machined aluminum nozzles
- Easy to read color coded two piece nameplates
- Corrosion resistant epoxy powder paint finish
- UL Listed and USCG Approved – meets D.O.T. requirements
- 12 year periodic hydrostatic test interval
- 6 year product warranty
- Available with hanger hook or brackets

Technical Data: Badger Halotron-1™ Stored Pressure Extinguisher Models

MODEL NUMBER	2.5 HB-1	5 HB-1	11 HB	15.5 HB
NOMINAL CAPACITY (LBS)	2.5	5	11	15.5
(KILOGRAMS)	1.14	2.27	5	7.05
UL FIRE RATING	2B:C	5B:C	1A-10B:C	2A-10B:C
EXTINGUISHING AGENT TYPE	HALOTRON-1	HALOTRON-1	HALOTRON-1	HALOTRON-1
ITEM PART NUMBER	23347	23348	23082	23097
VALVE MATERIAL	PLATED BRASS	PLATED BRASS	PLATED BRASS	PLATED BRASS
CYLINDER MATERIAL	STEEL	STEEL	STEEL	STEEL
SHIPPING WEIGHT (LBS)	6.85	10.6	23	26.5
(KILOGRAMS)	3.1	4.8	10.45	12.05
OPERATING PRESSURE	100 PSI	100 PSI	125 PSI	125 PSI
EXPELLANT	ARGON	ARGON	ARGON	ARGON
TEMPERATURE RANGE (F)	-40° to 120°	-40° to 120°	-40° to 120°	-40° to 120°
(C)	-40° to 49°	-40° to 49°	-40° to 49°	-40° to 49°
DISCHARGE TIME (SECONDS)	9	9	11	14
DISCHARGE RANGE (FEET)	6-10	9-15	9-15	12-18
(METERS)	1.83-3.05	2.74-4.57	2.74-4.57	3.66-5.49
UNIT HEIGHT (INCHES)	14.88	15.25	16.19	17.13
(CENTIMETERS)	37.8	38.74	41.12	43.51
UNIT WIDTH (INCHES)	6.13	6.13	8.35	8.75
(CENTIMETERS)	15.57	15.57	22.23	22.23
UNIT DEPTH (INCHES)	3	4.25	7.25	7.25
(CENTIMETERS)	7.62	10.8	18.42	18.42
USCG APPROVAL	N/A	Type B:C Size-I	Type B:C Size-I	Type B:C Size-II
BRACKET	MB-250 INCLUDED	MB-5 OPTIONAL	HB-11 OPTIONAL	HB-11 OPTIONAL

This information is subject to change without notice. Badger Fire Protection disclaims any liability for any errors or misinterpretation of the information contained therein. Contact Badger Fire Protection for your local distributor for assistance.

Distributed by:



Badger Fire Protection

4251 Seminole Trail • Charlottesville, VA 22911

Tel 800 446 3857 or 434 973 4361

Fax 800 248 7809 or 434 973 1589

www.badgerfire.com