CHEMWET, Wetting Agent CW

Chemguard CHEMWET is a highly concentrated wetting and penetrating agent, which reduces the surface tension of water. The reduction of the surface tension allows for quicker extinguishment and reducing water requirements. CHEMWET is designed for proportioning at 0.05% (one gallon of CHEMWET to 2,000 gallons of water). The CHEMWET formula contains anti-rust and anti-scaling agents as well as friction reducers, which improves the longevity of storage tanks and increases the performance of application.

FEATURES

Excellent wetting characteristics when used in combating Class “A” type fuel fires.

PROPORTIONING

Chemguard CHEMWET is suitable for use with the following types of proportioning equipment:

- Pre-mix
- In-line eductor

TYPICAL PROPORTIONING

Appearance……..……..Colorless Liquid
Specific gravity……..……1.05
pH……..……7-8
Viscosity……..……25 cps

ENVIRONMENTAL IMPACT

Chemguard CHEMWET is biodegradable, low in toxicity and can be treated in sewage treatment plants. CHEMWET concentrate is not manufactured with raw materials that are listed as reportable on any Federal Register.

STORAGE

If kept in the original unopened and airtight Chemguard supplied container and storage within the temperature range 35ºF - 120ºF an indefinite shelf life can be expected. If frozen, thawing will render CHEMWET completely serviceable again.

ORDERING INFORMATION & WEIGHTS

Part No:	Container	Weight
CWP	5-Gallon Pail / 19 Liters	45 lbs.
CWD	55-Gallon Drum / 208 Liters	495 lbs.

CHEMGUARD
204 S. 6th Ave • Mansfield, Tx 76063 • (817) 473-9964 • (817) 473-0606
www.chemguard.com

CHEMGUARD
204 S. 6th Ave • Mansfield, Tx 76063 • (817) 473-9964 • (817) 473-0606
www.chemguard.com