


GOMTEX®



CONSTRUCTION:

Inner and outer layer

Specially formulated rubber, I extruded through a circular woven. Low pressure drop thanks to its smooth inner wall. High thermal resistance.

Intermediate textile reinforcement

Jacket made of circular loom with yarn high tenacity polyester. Free from defects such as broken threads, knots, etc..

AVAILABLE LENGTHS:

60m, 30m, 25m, 23m, 20m, 18m, 15m. Other lengths up to 150 meters on request.

FEATURES:

Excellent abrasion resistance and intensive use by professionals. High resistance to oil, gasoline and a wide range of chemicals. Highly resistant to heat both the contact and radiant heat. Light hose flexible even at low temperatures (-15 ° C). Easy to handle and wind up thanks to its great flexibility. Highly resistant to breakage thanks to its special textile construction. No maintenance or drying. Easy to repair thanks to our repair system. Available with various international certifications.

FIELD OF APPLICATIONS:

Suitable for firefighters and professional services industry. Refineries. Army. Airports. Ships and oil platforms. Heavy industry.

OPTIONS:

Special colors like yellow, blue, green NATO, orange, gray low minimum order. Special marking with custom IDs. Packaging according to own specifications. They can be served with all kinds of international connections (Storz, Guillemín, BS, Barcelona, UNI, Nakajima, NOR, etc..).

SPECIFICATIONS:

Diameter		Weight	Thickness	pressure work	pressure break
inches	mm.	gr/m.	mm.	bars	bars
1"	25	245	2,2	30	>90
1 ¼"	32	310	2,2	30	>80
1 ½"	38	375	2,2	20	>62
1 2/3"	42	395	2,3	20	>62
1 ¾"	45	395	2,3	20	>62
2"	52	470	2,3	20	>60
2 1/6"	55	490	2,3	18	>55
2 ½"	64	600	2,3	17	>52
2 ¾"	70	650	2,3	17	>50
3"	75	750	2,4	17	>50
3 ¼"	80	760	2,4	17	>50
3 ½"	90	920	2,5	15	>50
4"	102	1.070	2,6	15	>50
4 1/3"	110	1.160	2,6	15	>45
4 ½"	115	1.180	2,6	15	>45
5"	125	1.425	2,8	15	>45
6"	152	1.700	3,0	13	>40